



Adjustable Coupling



Adjustable survey height



Foldable fibreglass beam



Shock absorbent hinge mechanism.



MALÅ RoadCart

The RoadCart from MALÅ is a dedicated cart designed for high speed road measurements utilizing one or two shielded GPR antennas. The RoadCart was designed in cooperation with experienced road investigation specialists to ensure safe and optimal performance at high speeds.

The MALÅ RoadCart is constructed with a foldable fibreglass beam to simplify transportation and shipping. This construction also enable users to shorten the RoadCart beam when performing single antenna measurements.

The RoadCart is adjustable for optimal road clearance and various towing hook heights, thus offering a level and smooth ride for the antennas, even at high speed.

Special spring loaded fixings hold the antennas securely in place on the RoadCart beam, however, should the antenna strike an obstacle in the road during data collection, these mechanisms are designed to move the antenna upwards and backwards to minimize impact shock.

System Set-up

The MALÅ RoadCart is typically configured with one high frequency antenna (1.2, 1.6 or 2.3 GHz) and one lower frequency antenna (250, 500 or 800 MHz) allowing the user to gather information from a range of depths to include the entire road construction, i.e. pavement, supportive layers and base.

MALÅ recommends using the RoadCart with our Professional Explorer (ProEx) system. The ProEx is a dual channel system and can therefore operate two antennas simultaneously at high speed, making it perfectly compatible with optimal RoadCart antenna set-up.


For single antenna use, the RoadCart can also be used with Malå's CX (using 1.2, 1.6 or 2.3GHz antenna) or X3M Control Unit (using 250, 500 or 800MHz antenna)

Features

The design and construction of the RoadCart is made for everyday usage featuring:

- Shock absorbent design to protect antennas
- Fully adjustable to optimize data collection
- Flexible design supporting various coupling heights
- Compact and foldable construction for easy transportation

Note: the RoadCart should always be used in accordance with any relevant local, national or regional legislation or guidelines.



Technical Specification

Dimensions (cm)

Unpacked: 130 (L) x 30 (W) x 50 (D)

Shipping box: 140 (L) x 40 (W) x 55 (D)

Weight (kg)

Unpacked: 21

Packed (box): 37

Wheel size: 16"

Wheel type: puncture proof

Distance encoder: included

See our webpage for latest information.

Head Office

MALÅ GeoScience AB
Skolgatan 11, SE-930 70
Malå, Sweden
Phone: +46 953 345 50
Fax: +46 953 345 67
E-mail: sales@malags.com

Your Distributor

GPRtech – Australian MALA GPR Distributor

4/105A Ben Boyd Road, Neutral Bay, NSW 2089, AUSTRALIA
Tel: +61 0438 278 902 | Fax: +61 02 9908 1484
Web: www.malagpr.com.au | Email: sales@malagpr.com.au